

MARBLE FREE- LENGTH



The free-length size module is available in a Patinato finish, which is obtained by brushing the stone until it has a natural, worn feel. The Patinato finish creates a charming aged look that adds discreet elegance for any area of your home. The sizes of the free-length pattern are of a set width, but a variable length, resulting in a staggered linear effect.



CAPE TOWN 021 506 1300 | GAUTENG 011 704 6827
KNYSNA 044 382 3632 | DURBAN 031 566 6562

www.naturalstonewarehouse.com

MARBLE FREE- LENGTH

SIZES

Natural Stone Warehouse's range of Free-Length products are supplied with a fixed widths and various lengths.

Due to the nature of the product, these lengths may vary from batch to batch, however the use of an experienced tiler will ensure the desired random laying pattern is achieved.

RECOMMENDED APPLICATIONS

Patinato Marble can be used in both interior and exterior applications.

The brushing process used in Patinato Marble enhances the natural veining characteristics of the product, giving it a unique surface texture and aged appearance.

Due to the uneven surface the product is more slip resistant than the polished finish but for external applications we further recommend an acid treatment to increase slip resistance.

As this is a natural product, one can expect slight variation between batches. Please arrange a product preview, either by photograph, or at one of our distribution centres in order to view the current stock.

LAYING RECOMMENDATION

- A 5mm joint between tiles - We do not recommend butt joining tiles
- The use of white tile adhesive
- White Pearl - Ivory grout or grout colour to individual taste
- Crema Marfil - Travertine grout or grout colour to individual taste
- Marron Emperador - Mid Brown grout or grout colour to individual taste
- Rojo Alicante - Mix of Ivory and Mid Brown grout or grout colour to individual taste
- No acid is to be used in the removing of grout/adhesive residue
- Existing expansion joints are to be respected and not tiled over
- Use expansion joints as prescribed by architect or specialized tiler
- Tiles should be laid on a level and even screed which should have been cured for about one week before tiling
- Naturally each piece is unique in veining and tonality therefore the onus rest with the installer to ensure blending is done correctly before laying the tiles to achieve your desired effect.

PRODUCT CARE AND MAINTENANCE

All natural stone tiles should be sealed to prevent staining. The laid tiles should be washed with Stone Shield Deep Clean which is a stone detergent. The tiler must ensure that no grout or adhesive is allowed to dry on the tile surface. After washing and rinsing the stone must be left to dry completely including grouting. As an anti-stain treatment we recommend the use of Stone Shield Marble, Granite and Travertine sealer. The product must be applied by professionals or under the strict instruction as indicated by the manufacturer. Sealers may cause enhancement of the natural colours of the stone depending on the stone type and the sealer used. Please speak to a consultant should you wish to have a demonstration of the finished product.

For everyday maintenance we recommend Stone Shield Daily Clean or a neutral Ph detergent. Do not use acid or alkaline detergents as repeated application will damage the sealer leaving the stone unprotected.

Remember to ask us about your warranty options.



The colours shown on this spec sheet are as exact as photographic and printing processes as well as screen resolution allow. We recommend that all colours are chosen from actual product samples available on request.

Pioneers in the art of elegant living.